

# Mikroschalter Produkt Übersicht **herga**

Technology Ltd

Series	Image	Model	Max. operating force (g)	Function	Tag type	Temp. range	Mech. Service Life	Elec. Rating (125/250 VA)	IP sealing	Certification	
										UL/cUL	ENEC
DF3		DF3-03	13...150	SPDT, SPST NO/NC	C, D, E, P	-40..85 °C	min. 5 Mio	3A	n.a.	x	x
		DF3-S3	13...150	SPDT, SPST NO/NC	C, D, E, P	-40..85 °C	min. 5 Mio	3A	n.a.	x	x
		DF3-05	13...150	SPDT, SPST NO/NC	C, D, E, P	-40..85 °C	min. 5 Mio	5A	n.a.	x	x
DF-M		DF-01	13...150	SPDT, SPST NO/NC	A, C, D, E, F, H, P	-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	x
		DF-03	13...150	SPDT, SPST NO/NC	A, C, D, E, F, H, P	-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	x
		DF-G3	13...150	SPDT, SPST NO/NC	A, C, D, E, F, H, P	-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	none
		DF-D3	13...150	SPDT, SPST NO/NC	A, C, D, E, F, H, P	-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	none
DFW		DFW-P1	15...170	SPDT, SPST NO/NC	C, D, E, P	-40..85 °C	min. 1 Mio	0,1...5 A	water proof button	x	x
		DFW-05	15...170	SPDT, SPST NO/NC	C, D, E, P	-40..85 °C	min. 1 Mio	0,1...5 A	water proof button	x	x
DFW-IP67		DFW-P1	15...170	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...5 A	IP67	x	x
		DFW-05	15...170	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...5 A	IP67	x	x
DS		DS	75...150	SPST NO	D, L, P, R	-40..85 °C	min. 3 Mio	0,05...0,1 A	n.a.	x	x
DW		DW-N2S	130...195	SPDT, SPST NO/NC	A, C, D, P	-40..85 °C	min. 0,5 Mio	0,1...3 A	n.a.	x	x
		DW-N3S	130...195	SPDT, SPST NO/NC	A, C, D, P	-40..85 °C	min. 0,5 Mio	0,1...3 A	n.a.	x	x
DW-IP67		DW-N2S		SPDT, SPST NO/NC	cable	-40..85 °C	0,5 Mio	0,1...3 A	IP67	x	x
		DW-N3S		SPDT, SPST NO/NC	cable	-40..85 °C	0,5 Mio	0,1...3 A	IP67	x	x
DW2		DW2-03	95...220	SPDT, SPST NO/NC		-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	x
		DW2-G3	95...220	SPDT, SPST NO/NC		-40..85 °C	min. 1 Mio	0,1...3 A	n.a.	x	x
DW2-IP67		DW-N2S	95...220	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...3 A	IP67	x	x
		DW-N3S	95...220	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...3 A	IP67	x	x




# Mikroschalter Produkt Übersicht **herga**

Technology Ltd

Series	Image	Model	Max. operating force (g)	Function	Tag type	Temp. range	Mech. Service Life	Elec. Rating (125/250 VA)	IP sealing	Certification	
										UL/cUL	ENEC
SM1	 External snap-fit lever	SM1-G1	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C	all series for H force: no define life cycles	0.1A	n.a.	x	x
		SM1-NC1	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C	all series for F Force: min. 1 Mio	0.1A	n.a.	x	x
		SM1-GC1	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C	others: min. 5 Mio	0.1A	n.a.	x	x
		SM1-N3	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		3A	n.a.	x	x
	 Internal lever	SM1-G3	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		3A	n.a.	x	x
		SM1-NC3	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		3A	n.a.	x	x
		SM1-GC3	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		3A	n.a.	x	x
		SM1-N6	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		6(3)A	n.a.	x	x
		SM1-G6	12...355	SPDT, SPST NO/NC	A, B, C, D, G, P	-40..125 °C		6(3)A	n.a.	x	x
SW2		SW2-C1	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	n.a.	x	x
		SW2-C3	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	n.a.	x	x
		SW2-06	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	n.a.	x	x
		SW2-10	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	n.a.	x	x
		SW2-H10	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	n.a.	x	x
SW2 IP40		SW2-C1	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	water proof button	x	x
		SW2-C3	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	water proof button	x	x
		SW2-06	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	water proof button	x	x
		SW2-10	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	water proof button	x	x
		SW2-H10	23...300	SPDT, SPST NO/NC	A, B, G, P	-40..125 °C	min. 2 Mio	0,1...10 A	water proof button	x	x
SW2 IP67		SW2-C1	23...300	SPDT, SPST NO/NC	cable	-40..125 °C	min. 2 Mio	0,1...10 A	IP67	x	x
		SW2-C3	23...300	SPDT, SPST NO/NC	cable	-40..125 °C	min. 2 Mio	0,1...10 A	IP67	x	x
		SW2-06	23...300	SPDT, SPST NO/NC	cable	-40..125 °C	min. 2 Mio	0,1...10 A	IP67	x	x
		SW2-10	23...300	SPDT, SPST NO/NC	cable	-40..125 °C	min. 2 Mio	0,1...10 A	IP67	x	x
		SW2-H10	23...300	SPDT, SPST NO/NC	cable	-40..125 °C	min. 2 Mio	0,1...10 A	IP67	x	x

# Mikroschalter Produkt Übersicht **herga**

Technology Ltd

Series	Image	Model	Max. operating force (g)	Function	Tag type	Temp. range	Mech. Service Life	Elec. Rating (125/250 VA)	IP sealing	Certification	
										UL/cUL	ENEC
VA2		VA2-P1	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-03	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-06	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-10	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-16	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-20	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-26	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-A03	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-A06	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
		VA2-T6	4...330	SPDT, SPST NO/NC	# 187, #250	-40..125 °C	min. 1 Mio	0,1...26 A	n.a.	x	x
VW1		VW1-P1	15...300	SPDT, SPST NO/NC	# 187	-40..85 °C	min. 1 Mio	0,1...10 A	water proof button	x	x
		VW1-03	15...300	SPDT, SPST NO/NC	# 187	-40..85 °C	min. 1 Mio	0,1...10 A	water proof button	x	x
		VW1-06	15...300	SPDT, SPST NO/NC	# 187	-40..85 °C	min. 1 Mio	0,1...10 A	water proof button	x	x
		VW1-10	15...300	SPDT, SPST NO/NC	# 187	-40..85 °C	min. 1 Mio	0,1...10 A	water proof button	x	x
VW1 IP67		VW1-P1	15...300	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...10 A	IP67	x	x
		VW1-03	15...300	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...10 A	IP67	x	x
		VW1-06	15...300	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...10 A	IP67	x	x
		VW1-10	15...300	SPDT, SPST NO/NC	cable	-40..85 °C	min. 1 Mio	0,1...10 A	IP67	x	x